# POWERTEST 1557

# MULTI FUNCTION INSTALLATION TESTER



Thanks to a clever bit of design, we have included a cordless probe for use with the tester, meaning you can hold the tester and see the results at the same time. Weighing in at a mere 900 grams, it's light too. And it can do any test that you require at the turn of a knob, including Earth Continuity, Insulation (100v, 250v, 500v), Non-trip Loop Impedance, Line Impedance, RCD trip line, RCD trip current and voltage / frequency measurements.

## **Key Features**

# COMPREHENSIVE TESTING FEATURES

Comprehensive 16th edition and Part-P testing features allow for a multitude of tests including: Earth Continuity, Insulation (100v, 250v, 500v), Non-trip Loop Impedance, Line Impedance, RCD Trip current, and Voltage/Frequency measurement.

## UNIQUE CORDLESS PROBE

Makes testing a breeze as it allows you a free hand to hold your tester - therefore you can view your results, as you're testing.

### NON-TRIPPING LOOP

Measure loop impedance without tripping RCD's.

# SMALLEST AND LIGHTEST IN ITS CLASS

It fits in the palm of your hand and won't weigh you down.

### **PowerSolution Users**

- ELECTRICAL CONTRACTORS
- ELECTRICAL ENGINEERS
- TRAINING INSTITUTIONS



Web: www.seaward.co.uk Email: sales@seaward.co.uk

#### **POWERTEST 1557 SPECIFICATIONS**

#### **SPECIFICATION**

**Earth Continuity** 

Test Current >200mA

Display Range 0.00ohms - 199ohms
Resolution 0.01ohms maximum

Test Lead Compensation Null lead resistance 0.00ohms - 10.00ohms

Live Circuit Detection Test inhibit if >30V detected

Insulation Resistance

Test Voltage 100V, 250V, 500V

Display Range 0.05Mohms – 199Mohms

Resolution 0.01Mohms maximum

Live Circuit Detection Test inhibit if >30V detected

Loop/Line Impedance

Supply Voltage 195 – 253V/440V, 45Hz – 65Hz

Test Current 15mA (non tripping for RCD protected circuits)

Display Range 0.01ohms - 2000ohms
Resolution 0.01ohms maximum
Loop Impedance Phase to Earth

Line Impedance Phase to Neutral/Phase to Phase

PFC/PSC Range 0 – 26kA

**RCD Trip Time** 

 Supply Voltage
 195 − 253V, 45 − 65Hz

 Test Currents
 10, 30, 100, 300, 500mA

 Trip Time Ranges
 0ms − 2000ms at  $1/2 I \triangle n$ 

0ms – 300ms at I∆n general 0ms – 500ms at I∆n selective 0ms – 40ms at 5x I∧n

and 180°

RCD Type General (G), Selective (S), Pulsed (A), AC (AC)

**RCD Trip Current (Ramp Test)** 

 Supply Voltage
 195 − 253V, 45 − 65Hz

 Test Currents
 10, 30, 100, 300, 500mA

 Ramp Current Range
 1/2 I△n to 1.1 I△n

Voltage/Frequency Measurement

Display Range 0 - 440V Resolution 1V Frequency Measuring Range 45 - 65Hz

Compliance IEC 61010-1 300V CAT III, EN 61557

Dimensions 260 x 100 x 55

Weight 950g

Power Supply 6 x AA Alkaline (supplied), 6 xx AA NiMH

Rechargeable (Optional)

## PowerSolutions Package

PowerSolutions is a total solutions philosophy that encompasses all aspects of installation testing, from the testers themselves to the information management software

When the tester and software are used in conjunction, the resulting PowerSolution gives you everything needed to run an efficient and effective installation testing business and meet all 16th edition and Part P requirements.

#### PowerSolutions Package includes:

- PowerTest 1557
- PowerGuard Pro PC based software
- PowerGuard Pro Mobile PDA based software

#### Supplied with:

- 2 year warranty
- 6 x 1.5V cells LR6 type AA alkaline batteries
- Test lead, 1.5M 13A UK plug to Red, Black, Green 4mm shrouded safety plugs
- Alligator Clips: Red, black, green
- Test lead, set 1.5M Red, Black, Green 4mm shrouded safety plugs to Red, Black, Green 4mm shrouded safety test probes
- Red, cordless, 4mm shrouded safety test probe

# **Optional Extras**

#### Software:



### Services:

SERVICE & CALIBRATION JUMP START



Seaward test and measurement companies include:



